



*"If you can imagine it, Nadco will make it stick."*

**3802**  
**(Transfer Tape)**

**Description:**

A 2 mil (50 micron) glass reinforced transfer tape with an aggressive acrylic pressure sensitive transfer adhesive and excellent oxidation and ultraviolet light resistance. Designed for both interior and exterior applications. This transfer film has good quick stick and high shear properties, and wets out to metals, high surface energy plastics, most elastomers and treated olefins and coated and plain papers.

**Applications:**

A high performance splicing tape designed for flying splices of lightweight papers to heavy weight board. Excellent temperature resistance. For use with nameplates, decals, aluminum, polyester, vinyls, polycarbonates, and papers. The initial quick stick allows for easy liner removal in paper splicing applications. Also, miscellaneous bonding, holding, laminating and mounting.

**Technical Data**

	<b>Imperial</b>	<b>Metric</b>
<b>Adhesive thickness:</b>	2 mils (0.0020")	0.0508 mm
<b>Peel Adhesion: (PSTC-1):</b>	30 oz/in width	8.3 N/2.5 cm
<b>Shear Adhesion: (PSTC-7):</b>	100+ hours @ 2.2 psi	100+ hours @ 15.2 kPa
<b>Maximum continuous use Temperature:</b>	300°F	149°C
<b>Minimum application temperature:</b>	-10°F	-23°C
<b>Release Liner:</b>	55 lb	90 GSM
	Glassine liner	